



Max One, is the new maxi screen from Adeo Screen renewed and perfected, it comes with open casing underneath, also available with optional "casing closure", to close off the housing completely.

Max One is the solution for very large projection, used for large scale applications.

Designed for practical installation, thanks to quick and easy assembly system.

The screen is also equipped with a safety roller fall system to avoid in any case the fall of the rolling tube.



See page **93**
for Technical data

Create your own screen with the PSS

- > **Personalized dimensions:** width and height
- > **Motor type:** standard motor
- > **Case:** available only with case
- > **Case color:** standard in White Grinz. Optional in Black Grinz. Custom color for an extra cost
- > **Projection surface fall:** back (standard), front or reverse-roll (optional)
- > **Side of command/motor:** right (standard) or left (optional)

Projection Surfaces (see page 6)

- > Vision White
- > Vision Acoustik / Vision Macro Acoustik

Standard Accessories

- > Kit with wall or ceiling installation brackets
- > Unipolar switch

Optional Accessories

- > Interface to drive the screen in radio frequency with remote control (not included), 12V trigger, unipolar switch, dry contact or RS232
- > Receiver and infrared remote control
- > Casing closure option
- > Extension brackets for screens up to 60 cm



PSS Formats

1:1	1.33:1	1.60:1	1.78:1	2.35:1	2.37:1	2.39:1	2.40:1
	4:3	16:10	16:9	21:9			

Max One Without borders

Aspect ratio	Viewing Width	Viewing Height	Diagonal Inches	Overall Width	Overall Height	Packaging Dimensions	Net Weight	Gross Weight
	C	D	N	A	B	mm	kg	kg
1,00 (1:1)	5000	5000	278	5100	5226	5280x290x320	80	105
	5500	3759	246	5100	3985	5280x290x320	76	101
1,33 (4:3)	5500	4135	271	5600	4361	5780x290x320	84	109
	6000	4511	296	6100	4737	6280x290x320	92	117
	6500	4887	320	6600	5113	6780x290x320	103	123
1,60 (16:10)	5000	3125	232	5100	3351	5280x290x320	74	99
	5500	3438	255	5600	3664	5780x290x320	82	107
	6000	3750	279	6100	3976	6280x290x320	90	115
	6500	4063	302	6600	4289	6780x290x320	101	126
1,78 (16:9)	5000	2809	226	5100	3035	5280x290x320	74	99
	5500	3090	248	5600	3316	5780x290x320	82	107
	6000	3371	271	6100	3597	6280x290x320	90	115
	6500	3652	294	6600	3878	6780x290x320	101	126
2,35 (21:9)	5000	2128	214	5100	2354	5280x290x320	73	98
	5500	2340	235	5600	2566	5780x290x320	81	106
	6000	2553	257	6100	2779	6280x290x320	89	114
2,37	6500	2766	278	6600	2992	6780x290x320	100	125
	5000	2110	214	5100	2336	5280x290x320	73	98
	5500	2321	235	5600	2547	5780x290x320	81	106
	6000	2532	256	6100	2758	6280x290x320	89	114
2,39	6500	2743	278	6600	2969	6780x290x320	100	125
	5000	2092	213	5100	2318	5280x290x320	73	98
	5500	2301	235	5600	2527	5780x290x320	81	106
	6000	2510	256	6100	2736	6280x290x320	89	114
2,40	6500	2720	277	6600	2946	6780x290x320	100	125
	5000	2083	213	5100	2309	5280x290x320	73	98
	5500	2292	235	5600	2518	5780x290x320	81	106
	6000	2500	256	6100	2726	6280x290x320	89	114
2,40	6500	2708	277	6600	2934	6780x290x320	100	125

Custom sizes are available upon request



30 mm lower bar is used on screens with viewing width of 6500 mm



Surface Fireproof Certifications